



Fig.41

Fig. No.	Description	Part No.	Qty.
	<u>Instrument panel</u>		
40- 9	<u>Windshield frame</u> , cpl., with instrument panel	95996 ^{1*)}	
40-10	. <u>Instrument panel</u> , cpl.	94531*	1
40-11	. . <u>Instrument panel</u> , inner plating	94514*	1
40-12	. Windshield member	95985*	1
	. Windshield pillar, L	95987	1
	. Windshield pillar, R	95988	1
41- 1	<u>Locker</u> on instrument panel	94522	1
41- 2	Screw, self-tapping, l = 3/8"	106938	3
41- 3	Base washer	120098	3
41- 4	Screw, self-tapping, l = 1/2"	106927	4
41- 5	Speed nut	90493	4
41- 6	<u>Lid</u> for locker	94532	1
41- 7	Moulding	94520	1
41- 8	<u>Anchorage</u>	94924	2
41- 9	<u>Hinge</u> , cpl.	94524	1
	. <u>Spring</u> , L	94526	1
	. <u>Spring</u> , R	94527	1
41-10	Screw	115494	2
41-11	Lock washer	951693	2
41-12	Screw	106938	4
	Rubber cushion for locker lid	657137	2
	<u>Catch for locker</u> , consisting of:		
41-13	. Push button	94762	1
41-14	. Spring	86553	1
41-15	. Tongue	92856	1
41-16	. Spring	92956	1
41-17	. Screw	14012	2
41-18	. Spring washer	906983	2
41-19	Striker plate	94535	1
41-20	Screw, self-tapping	955125	2
41-21	Rubber cushion	93963	2
	<u>Ash-tray</u> , cpl., on instrument panel, Alt.2, black finger grip	655303	1
41-22	. Spring	96921	1
41-23	. Cover	92373	1
41-24	. Pin	190143	1
41-25	. Finger grip, Alt.1, gray	94583	1
	. Finger grip, Alt.2, black	655304	1
41-26	. Rubber cushion	92375	2
41-27	. Retainer	92376	2
41-28	. Screw	115463	2

1. Replaced by 1 pc. 94531, 1 pc. 95985, 1 pc. 95987 and 1 pc. 95988.
* Included in complete body.

Fig. No.	Description	Part No.	Qty
41-29	<u>"444" emblem</u>	94815	1
41-30	Speed nut	82660	2
41-31	<u>Cover</u>	94760	1
41-32	Screw, self-tapping	190666	2
41-33	Speed nut	82660	2
	Rubber cushion	657137	2
41-34	<u>Moulding</u>	94519	1
41-35	Anchorage	94924	2
41-36	<u>Cigarette lighter, cpl.</u>	79832	1
41-37	. Sleeve	93932	1
41-38	. Glow element	93931	1
41-39	. Button	88592	1
41-40	. Washer	93554	1
	<u>Defroster mask on instrument panel</u>	95650	2
	Seal strip	13319	*
	Clamp	95685	8
	Screw	106987	8
	Nut	94107	8
	Washer	91944	8

* State required length.